

Supraflo Specification Table



SUPRAFLO Models						Filter Quantity	Total Supra-Netmax Filter Media Area		Valve Quantity	Module Quantity	Unit Weight		Compressed Air Consumption		Height	Width	Depth
							(FT2)	(M2)			(LBS)	(KGS)	SFC/PULSE	SCFM 6P/Min			
SFC	2	-	2	-	SD	2	510	47.4	2	1	954	433	1.7	10.2	7' 8"	2' 1"	5' 1"
SFC	4	-	2	-	SD	4	1020	94.8	4	1	1317	597	1.7	10.2	7' 8"	3' 11"	5' 1"
SFC	6	-	2	-	SD	6	1530	142.1	6	1	1726	783	1.7	10.2	7' 8"	5' 9"	5' 1"
SFC	8	-	2	-	H55	8	2040	189.5	4	1	1922	872	1.7	10.2	10' 3"	4' 1"	7' 2"
SFC	16	-	2	-	H55	16	4080	379.0	8	2	3237	1468	3.4	20.4	10' 3"	7' 10"	7' 2"
SFC	24	-	2	-	H55	24	6120	568.6	12	3	4552	2065	5.1	30.6	10' 3"	11' 7"	7' 2"
SFC	32	-	2	-	H55	32	8160	758.1	16	4	5947	2698	6.8	40.8	10' 3"	15' 4"	7' 2"
SFC	12	-	3	-	H55	12	3060	284.3	6	1	2420	1098	1.7	10.2	11' 11"	4' 1"	7' 2"
SFC	24	-	3	-	H55	24	6120	568.6	12	2	4016	1822	3.4	20.4	11' 11"	7' 10"	7' 2"
SFC	36	-	3	-	H55	36	9180	852.8	18	3	5612	2546	5.1	30.6	11' 11"	11' 7"	7' 2"
SFC	48	-	3	-	H55	48	12240	1137.1	24	4	7288	3306	6.8	40.8	11' 11"	15' 4"	7' 2"
SFC	60	-	3	-	H55	60	15300	1421.4	30	5	8884	4030	8.5	51	11' 11"	19' 1"	7' 2"
SFC	72	-	3	-	H55	72	18360	1705.7	36	6	10480	4754	10.2	61.2	11' 11"	22' 10"	7' 2"
SFC	16	-	4	-	H55	16	4080	379.0	8	1	2873	1303	1.7	10.2	13' 7"	4' 1"	7' 2"
SFC	32	-	4	-	H55	32	8160	758.1	16	2	4762	2160	3.4	20.4	13' 7"	7' 10"	7' 2"
SFC	48	-	4	-	H55	48	12240	1137.1	24	3	6651	3017	5.1	30.6	13' 7"	11' 7"	7' 2"
SFC	64	-	4	-	H55	64	16320	1516.2	32	4	8620	3910	6.8	40.8	13' 7"	15' 4"	7' 2"
SFC	80	-	4	-	H55	80	20400	1895.2	40	5	10509	4767	8.5	51	13' 7"	19' 1"	7' 2"
SFC	96	-	4	-	H55	96	24480	2274.3	48	6	12398	5624	10.2	61.2	13' 7"	22' 10"	7' 2"
SFC	112	-	4	-	H55	112	28560	2653.3	56	7	14367	6517	11.9	71.4	13' 7"	26' 7"	7' 2"
SFC	128	-	4	-	H55	128	32640	3032.4	64	8	16256	7374	13.6	81.6	13' 7"	30' 4"	7' 2"